

The SebaKMT HL50-BT is a simple compact acoustic leak detection system for water pipes

The system has an ergonomic grip shape that makes it a single hand operation. With only two operation buttons, the HL50-BT can be used simply by a thumb.

The HL50-BT has an integrated sensor and Bluetooth wireless headphones. This allows point location on internal leaks, as well as connection to additional sensors for use externally. The HL50-BT offers optimum mobility.

Features

- Easy to operate with only two buttons
- Frequency filter for different field applications
- Rechargeable batteries
- Can be extended with additional sensors



The HL50-BT comes with an extension set for use with a probe or magnet. But it can be extended for external use with three optional external microphones, a Universal microphone and tripod, a Piezo microphone, or a ground microphone.

The HL50-BT has a large LCD display screen that shows measured sound level simultaneously in numerical for and as a bar graph. In addition, the frequency filter is displayed. When a measurement has been completed, the previous measured sound level is indicated on the bar graph.



CONTACT OUR TEAM TODAY TO DISCUSS YOUR REQUIREMENTS
 01249 816181 > info@hmglocation.co.uk > www.hmglocation.co.uk

©2021 HMG Water Solutions Ltd. All rights reserved to make changes to design and specification without prior notice or consent. E&OE



SebaKMT HL50-BT Acoustic Above Ground Leak Detection

Water Solutions

Product	
Description	Part Number
HL50-BT Kit <i>Contains HL-50 -BT, Bluetooth Headphones, Case, Magnetic Adaptor, Extension rods, Charger</i>	301001
PAM B-2 Accessories Set <i>Contains, Universal microphone PAM B-2, Tripod accessories</i>	301002
PAM T-3-1 Accessories Set <i>Contains, Piezo microphone PAM T-3-1 accessories, Mounting bracket for HL50-BT at the feeler rod sensor, Foot traverse</i>	301003
PAM W-2 accessories Set <i>Contains, Ground microphone, carrying rod, connecting cable, Tripod adaptor</i>	301004

Product Specification	
Dimensions	90 x 185 x 60mm
Weight	400g
Power Supply	3.6V lithium battery (rechargeable)
Operating Time	>10 hours
Operating Temperature	-10°C to +50°C
Storage Temperature	-25°C to +70°C
Display	LCD, value 0 to 99
Memory	Last recorded value

CONTACT OUR TEAM TODAY TO DISCUSS YOUR REQUIREMENTS
01249 816181 > info@hmglocation.co.uk > www.hmglocation.co.uk

©2021 HMG Water Solutions Ltd. All rights reserved to make changes to design and specification without prior notice or consent. E&OE

