



SERVICECAM H₂O-PRO

Live access potable CCTV system

ServiceCam H2O PRO is a 14mm diameter camera on the end of 50m of 4.5mm diameter rigid fibreglass rod. The CCTV head has an in-built FAST PipeMic™ that allows the system to not only see inside the pipe, but to locate leaks as well. The ServiceCam H2O PRO has been designed for end on insertion in service pipes from 25mm in diameter, insertion vertically through a standpipe from an Elster (hockey stick type) meterbox, and vertically into small diameter mains from a saddle fitting or through bore hydrant.



- Faster - Speeds up pipe problem investigations and reduce time for customers to be off water
- Cheaper - Reduces maintenance costs
- Safer - Can be used with several safe under pressure access systems for insertion into live water pipes
- Leak Location - Able to show leak vortexes, weeping leaks and provide audio confirmation through ServiceCAM H2O Pro in-built FAST Pipemic
- Easier - This system comes with full training and support

- 14mm diameter camera
- 20m to 50m push rod capability
- Choice of 5.4" or 8" screen or a full recording 8"
- screen (12" option available)
- 8" recording screen includes text overlay and wifi
- WRAS approved material
- Chlorination tank included
- Designed for safe operation up to 10 bar
- Integrated FAST PipeMic™ for combined visual and acoustic leak detection
- Suitable for insertion into 25mm service pipes and small-diameter mains

INFO@SYNTHOTECH.CO.UK

+44 (0) 1423 816 060

INNOVATIVE ENGINEERING

WWW.SYNTHOTECH.COM



SYNTHOTECH